

TECHNICAL DATA SHEET

PRODUCT NAME: CARBOPUR 64

PRODUCT CODE: T196062

RELATED ARTICLES: E64BB550, E64BB600

DESCRIPTION

Extruded activated carbon.
Particle size: 4 mm

ANALYTICAL DATA

A / D	ANALYSIS DESCRIPTION	NOTE	MAX MIN TIP	VALUE	TOLERANCE	U. M.	ANALYTICAL METHOD
D	SPECIFICATIONS						
A	ADSORPTION CC14		MINIMUM	60		%	ASTM D 3467
A	MOISTURE (as packed)		MAXIMUM	5		%	ASTM D 2867
D	GENERAL PROPERTIES						
D	BUTANE ADSORPTION	(P/PO 0.42)	MINIMUM	20		%	ASTM D 5742
D	IODINE NUMBER		MINIMUM	900		mg/g	ASTM D 4607
D	SPECIFIC SURFACE AREA (BET)		MINIMUM	950		m2/g	ASTM D 3663
D	BULK DENSITY		MAXIMUM	550		kg/m3	ASTM D 2854
D	HARDNESS		MINIMUM	95		%	ASTM D 3802
D	ASHES		MAXIMUM	15		%	ASTM D 2866
D	pH	alkaline					ASTM D 3838

A/D = ANALYSIS / COMPLIANCE

FURTHER INFORMATION

The data contained in this TDS are based on the best technical knowledge and they are not binding. Brenntag guarantees the parameters contained in this TDS, and is not responsible for the performance of the products themselves in the applications of the end user.
Data provided by Brenntag's supplier

THIS DOCUMENT IS ELECTRONICALLY ISSUED AND NOT SIGNED IN

REVISION N° 00003 OF 13/01/2023